


## SMDJ-H Series

### General Information

The SMDJ-H series is designed to protect voltage sensitive components from high voltage, high energy transients. They have excellent clamping capability, high surge capability, low zener impedance and fast response time. The SMD-H series is supplied in YINT Semiconductor's exclusive, cost-effective, highly reliable and is ideally suited for use in communication systems, automotive, numerical controls, process controls, medical equipment, business machines, power supplies and many other industrial/consumer Applications.



Molded plastic  
glass passivated junction.

### Features

- Case: DO-214AB/SMC
- For surface mounted applications in order to optimize board space.
- Polarity: Color band denoted positive end (cathode) except Bidirectional.
- Typical failure mode is short from over-specified voltage or current
- High Temperature soldering: 260°C/10 seconds at terminals.
- Terminal: Solder plated, solderable per MIL-STD-750, Method 2026.
- AEC-Q101 qualified

### Applications

TVS devices are ideal for the protection of I/O Interfaces,  $V_{CC}$  bus and other vulnerable circuits used in Telecom, Computer, Industrial and Consumer electronic applications

### Electrical Characteristics (@ $T_A = 25^\circ \text{C}$ Unless Otherwise Noted)

Parameter	Symbol	Value	Unit
Minimum Peak Pulse Power Dissipation ( $T = 1 \text{ ms}$ ) (note1 note 2)	$P_{PK}$	3000	Watts
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method) (Note 3)	$I_{FSM}$	300	Amps
Steady State Power Dissipation @ $T_L = 75^\circ \text{C}$	$P_{M(AV)}$	6.5	Watts
Maximum Instantaneous Forward Voltage @ $I_{PP} = 50 \text{ A}$ (For Unidirectional Units Only)(note4 Note 5)	$V_F$	3.5/5	Volts
Operating Temperature Range	$T_J$	-55 to +150	$^\circ \text{C}$
Storage Temperature Range	$T_{STG}$	-55 to +150	$^\circ \text{C}$



1. Non-repetitive current pulse, per Pulse Waveform graph and derated above  $T_A = 25^\circ \text{C}$  per Pulse Derating Curve.
2. Thermal Resistance Junction to Lead.
3. 8.3 ms Single Half-Sine Wave duty cycle = 4 pulses maximum per minute (unidirectional units only).
4. Single Phase, Half Wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20 %.
5.  $V_F < 3.5 \text{ V}$  for  $V_{BR} < 200 \text{ V}$  and  $V_F < 5.0 \text{ V}$  for  $V_{BR} > 201 \text{ V}$ .

**Electrical Characteristics ( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)**

Part Number (Bi)	Part Number (Uni)	MARKING		Reverse Stand off Voltage $V_R$ (Volts)	Breakdown Voltage $V_{BR}$ (Volts)@ $I_T$		Test Current $I_T$ (mA)	Maximum Reverse Leakage $I_R$ @ $V_R$ ( $\mu$ A)	Maximum Peak Pulse Current $I_{pp}$ (A)	Maximum Clamping Voltage $V_C$ @ $I_{pp}$ (V)
		BI	UNI		Min .V	Max .V				
SMDJ5.0CA-H	SMDJ5.0A-H	DDEH	RDEH	5.0	6.40	7.00	10	800	326.1	9.2
SMDJ6.0CA-H	SMDJ6.0A-H	DDGH	RDGH	6.0	6.67	7.37	10	800	291.3	10.3
SMDJ 6.5CA-H	SMDJ 6.5A-H	DDKH	RDKH	6.5	7.22	7.98	10	500	267.9	11.2
SMDJ7.0 CA-H	SMDJ7.0 A-H	DDMH	PDMH	7.0	7.78	8.60	10	200	250.0	12.0
SMDJ 7.5CA-H	SMDJ 7.5A-H	DDPH	PDPH	7.5	8.33	9.21	1	100	232.6	12.9
SMDJ 8.0CA-H	SMDJ 8.0A-H	DDRH	PDRH	8.0	8.89	9.83	1	50	220.6	13.6
SMDJ8.5 CA-H	SMDJ8.5 A-H	DDTH	PDTH	8.5	9.44	10.40	1	20	208.3	14.4
SMDJ9.0 CA-H	SMDJ9.0 A-H	DDVH	PDVH	9.0	10.00	11.10	1	10	194.8	15.4
SMDJ10CA-H	SMDJ10A-H	DDXH	PDXH	10.0	11.10	12.30	1	5	176.5	17.0
SMDJ11CA-H	SMDJ11A-H	DDZH	PDZH	11.0	12.20	13.50	1	2	164.8	18.2
SMDJ12CA-H	SMDJ12A-H	DEEH	PEEH	12.0	13.30	14.70	1	2	150.8	19.9
SMDJ13CA-H	SMDJ13A-H	DEGH	PEGH	13.0	14.40	15.90	1	2	139.5	21.5
SMDJ14CA-H	SMDJ14A-H	DEKH	PEKH	14.0	15.60	17.20	1	2	129.3	23.2
SMDJ15CA-H	SMDJ15A-H	DEMH	PEMH	15.0	16.70	18.50	1	2	123.0	24.4
SMDJ16CA-H	SMDJ16A-H	DEPH	PEPH	16.0	17.80	19.70	1	2	115.4	26.0
SMDJ17CA-H	SMDJ17A-H	DERH	PERH	17.0	18.90	20.90	1	2	108.7	27.6
SMDJ18CA-H	SMDJ18A-H	DETH	PETH	18.0	20.00	22.10	1	2	102.7	29.2
SMDJ20CA-H	SMDJ20A-H	DEVH	PEVH	20.0	22.20	24.50	1	2	92.6	32.4
SMDJ22CA-H	SMDJ22A-H	DEXH	PEXH	22.0	24.40	26.90	1	2	84.5	35.5
SMDJ24CA-H	SMDJ24A-H	DEZH	PEZH	24.0	26.70	29.50	1	2	77.1	38.9
SMDJ26CA-H	SMDJ26A-H	DFEH	PFEH	26.0	28.90	31.90	1	2	71.3	42.1
SMDJ28CA-H	SMDJ28A-H	DFGH	PFGH	28.0	31.10	34.40	1	2	66.1	45.4
SMDJ30CA-H	SMDJ30A-H	DFKH	PFKH	30.0	33.30	36.80	1	2	62.0	48.4
SMDJ33CA-H	SMDJ33A-H	DFMH	PFMH	33.0	36.70	40.60	1	2	56.3	53.3
SMDJ36CA-H	SMDJ36A-H	DFPH	PFPH	36.0	40.00	44.20	1	2	51.6	58.1
SMDJ40CA-H	SMDJ40A-H	DFRH	PFRH	40.0	44.40	49.10	1	2	46.5	64.5
SMDJ43CA-H	SMDJ43A-H	DFTH	PFTH	43.0	47.80	52.80	1	2	43.2	69.4
SMDJ45CA-H	SMDJ45A-H	DFVH	PFVH	45.0	50.00	55.30	1	2	41.3	72.7
SMDJ48CA-H	SMDJ48A-H	DFXH	PFXH	48.0	53.30	58.90	1	2	38.8	77.4
SMDJ51CA-H	SMDJ51A-H	DFZH	PFZH	51.0	56.70	62.70	1	2	36.4	82.4
SMDJ54CA-H	SMDJ54A-H	DGEH	RGEH	54.0	60.00	66.30	1	2	34.4	87.1
SMDJ58CA-H	SMDJ58A-H	DGGH	PGGH	58.0	64.40	71.20	1	2	32.1	93.6
SMDJ60CA-H	SMDJ60A-H	DGKH	PGKH	60.0	66.70	73.70	1	2	31.0	96.8
SMDJ64CA-H	SMDJ64A-H	DGMH	PGMH	64.0	71.10	78.60	1	2	29.1	103.0
SMDJ70CA-H	SMDJ70A-H	DGPH	PGPH	70.0	77.80	86.00	1	2	26.5	113.0
SMDJ75CA-H	SMDJ75A-H	DGRH	PGRH	75.0	83.30	92.10	1	2	24.8	121.0
SMDJ78CA-H	SMDJ78A-H	DGTH	PGTH	78.0	86.70	95.80	1	2	23.8	126.0

SMDJ85CA-H	SMDJ85A-H	DGVH	PGVH	85.0	94.40	104.0	1	2	21.9	137.0
SMDJ90CA-H	SMDJ90A-H	DGXH	PGXH	90.0	100.0	111.0	1	2	20.5	146.0
SMDJ100CA-H	SMDJ100A-H	DGZH	PGZH	100.0	111.0	123.0	1	2	18.5	162.0
SMDJ110CA-H	SMDJ110A-H	DHEH	PHEH	110.0	122.0	135.0	1	2	16.9	177.0
SMDJ120CA-H	SMDJ120A-H	DHGH	PHGH	120.0	133.0	147.0	1	2	15.5	193.0
SMDJ130CA-H	SMDJ130A-H	DHKH	PHKH	130.0	144.0	159.0	1	2	14.4	209.0
SMDJ150CA-H	SMDJ150A-H	DHMH	PHMH	150.0	167.0	185.0	1	2	12.3	243.0
SMDJ160CA-H	SMDJ160A-H	DHPH	PHPH	160.0	178.0	197.0	1	2	11.6	259.0
SMDJ170CA-H	SMDJ170A-H	DHRH	PHRH	170.0	189.0	209.0	1	2	10.9	275.0
SMDJ180CA-H	SMDJ180A-H	IHTH	HHTH	180.0	201.0	222.0	1	2	10.3	292.0
SMDJ190CA-H	SMDJ190A-H	IHVH	HHVH	190.0	211.0	233.0	1	2	9.7	308.0
SMDJ200CA-H	SMDJ200A-H	IHXH	HHXH	200.0	224.0	247.0	1	2	9.3	324.0
SMDJ210CA-H	SMDJ210A-H	IHZH	HHZH	210.0	237.0	263.0	1	2	8.8	340.0
SMDJ220CA-H	SMDJ220A-H	IIIEH	HIEH	220.0	246.0	272.0	1	2	8.4	356.0

## I-V Curve Characteristics



Symbol	Parameter
$I_{PP}$	Maximum Reverse Peak Pulse Current
$V_C$	Clamping Voltage @ $I_{PP}$
$V_{RWM}$	Working Peak Reverse Voltage
$I_R$	Maximum Reverse Leakage Current @ $V_{RWM}$
$V_{BR}$	Breakdown Voltage @ $I_T$
$I_T$	Test Current

## Rating & Characteristic Curves





Figure 3- Typical Junction Capacitance




Figure 4- Pulse Waveform




Figure 5- Steady State Power Derating Curve






Figure 6- Pulse Rating Curve





## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

DO-214AB(SMC)




Mounting Pad Layout






### Part Numbering System



### Part Marking System



### Disclaimer

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.

Users should verify actual device performance in their specific applications.